

**Amendments to the Specification:**

Please replace the paragraphs beginning on page 17 at line 1 through line 7 of page 19 with the following amended paragraphs:

With reference to Figure 1, an exemplary system for implementing the invention includes a general purpose computing device in the form of a conventional computer 120, including a processing unit 121, a system memory 122, and a system bus 123 that couples various system components including the system memory 122 to the processing unit 121. The system bus 123 may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. The system memory includes read only memory (ROM) 124 and random access memory (RAM) 125. A basic input/output system (BIOS) 126, containing the basic routines that help transfer information between elements within the computer 120, such as during start-up, may be stored in ROM 124.

The computer 120 may also include a magnetic hard disk drive 127 for reading from and writing to a magnetic hard disk 139, a magnetic disk drive 128 for reading from or writing to a removable magnetic disk 129, and an optical disk drive 130 for reading from or writing to removable optical disk 131 such as a CD-ROM or other optical media. The magnetic hard disk drive 127, magnetic disk drive 128, and optical disk drive 130 are connected to the system bus 123 by a hard disk drive interface 132, a magnetic disk drive-interface 133, and an optical drive interface 134, respectively. The drives and their associated computer-readable media provide nonvolatile storage of computer-executable instructions, data structures, program modules and other data for the computer 120. Although the exemplary environment described herein employs a magnetic hard disk 139, a removable magnetic disk 129 and a removable optical disk 131, other types of computer readable media for storing data can be used, including magnetic cassettes, flash memory cards, digital video disks, Bernoulli cartridges, RAMs, ROMs, and the like.

Program code means comprising one or more program modules may be stored on the hard disk 139, magnetic disk 129, optical disk 131, ROM 124 or RAM 125, including an operating system 135, one or more application programs 136, other program modules 137, and program data 138. A user may enter commands and information into the computer 120 through keyboard 140, pointing device 142, or other input devices (not shown), such as a microphone, joy stick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit 121 through a serial port interface 146 coupled to system bus 123. Alternatively, the input devices may be connected by other interfaces, such as a parallel

port, a game port or a universal serial bus (USB). A monitor 147 or another display device is also connected to system bus 123 via an interface, such as video adapter 148. In addition to the monitor, personal computers typically include other peripheral output devices (not shown), such as speakers and printers.

The computer 120 may operate in a networked environment using logical connections to one or more remote computers, such as remote computers 149a and 149b. Remote computers 149a and 149b may each be another personal computer, a server, a router, a network PC, a peer device or other common network node, and typically include many or all of the elements described above relative to the computer 120, although only memory storage devices 150a and 150b and their associated application programs 136a and 136b have been illustrated in Figure 1. The logical connections depicted in Figure 1 include a local area network (LAN) 151 and a wide area network (WAN) 152 that are presented here by way of example and not limitation. Such networking environments are commonplace in office-wide or enterprise-wide computer networks, intranets and the Internet.

When used in a LAN networking environment, the computer 120 is connected to the local network 151 through a network interface or adapter 153. When used in a WAN networking environment, the computer 120 may include a modem 154, a wireless link, or other means for establishing communications over the wide area network 152, such as the Internet. The modem 154, which may be internal or external, is connected to the system bus 123 via the serial port interface 146. In a networked environment, program modules depicted relative to the computer 120, or portions thereof, may be stored in the remote memory storage device. It will be appreciated that the network connections shown are exemplary and other means of establishing communications over wide area network 152 may be used.